

GeoFlex Exhaust (170°C – briefly 200°C)

EPDM / PP plastic coil



Use: Extraction of exhaust fumes
and welding smoke.
(May be run over to a certain extent)

Art. No.	Description	Weight	Bend
09-075A	GeoFlex Exhaust ø76 – 5 m pcs.	2,7 kg	73 mm
09-075B	GeoFlex Exhaust ø76 – 7,5 m pcs.	4,1 kg	73 mm
09-075C	GeoFlex Exhaust ø76 – 10 m pcs.	5,4 kg	73 mm
09-075D	GeoFlex Exhaust ø76 – 15 m pcs.	8,2 kg	73 mm
09-076A	GeoFlex Exhaust ø102 – 5 m pcs.	3,6 kg	71 mm
09-076B	GeoFlex Exhaust ø102 – 7,5 m pcs.	5,3 kg	71 mm
09-076C	GeoFlex Exhaust ø102 – 10 m pcs.	7,2 kg	71 mm
09-076D	GeoFlex Exhaust ø102 – 15 m pcs.	10,6 kg	71 mm
09-077A	GeoFlex Exhaust ø127 – 5 m pcs.	4,4 kg	89 mm
09-077B	GeoFlex Exhaust ø127 – 7,5 m pcs.	6,5 kg	89 mm
09-077C	GeoFlex Exhaust ø127 – 10 m pcs.	8,8 kg	89 mm
09-077D	GeoFlex Exhaust ø127 – 15 m pcs.	13,0 kg	89 mm
09-078A	GeoFlex Exhaust ø152 – 5 m pcs.	5,2 kg	106 mm
09-078B	GeoFlex Exhaust ø152 – 7,5 m pcs.	7,8 kg	106 mm
09-078C	GeoFlex Exhaust ø152 – 10 m pcs.	10,4 kg	106 mm
09-078D	GeoFlex Exhaust ø152 – 15 m pcs.	15,6 kg	106 mm
09-079A	GeoFlex Exhaust ø200 – 5 m pcs.	6,9 kg	143 mm
09-079B	GeoFlex Exhaust ø200 – 7,5 m pcs.	10,3 kg	143 mm
09-079C	GeoFlex Exhaust ø200 – 10 m pcs.	13,8 kg	143 mm
09-079D	GeoFlex Exhaust ø200 – 15 m pcs.	20,6 kg	143 mm

(May be run over to a certain extent)

GeoFlex Exhaust 220 (op til 220°C)

TPE w/steel coil



Use: Extraction of exhaust fumes
and welding smoke.
It is not crushproof.

Art. No.	Description	Weight	Bend
09-095A	GeoFlex Exhaust-220 ø76 mm x 5 meters pcs	2,4 kg	55 mm
09-095B	GeoFlex Exhaust-220 ø76 mm x 7,5 meters pcs	3,6 kg	55 mm
09-095C	GeoFlex Exhaust-220 ø76 mm x 10 meters pcs	4,8 kg	55 mm
09-095D	GeoFlex Exhaust-220 ø76 mm x 15 meters pcs	7,2 kg	55 mm
09-096A	GeoFlex Exhaust-220 ø102 mm x 5 meters pcs	3,3 kg	45 mm
09-096B	GeoFlex Exhaust-220 ø102 mm x 7,5 meters pcs	4,9 kg	45 mm
09-096C	GeoFlex Exhaust-220 ø102 mm x 10 meters pcs	6,6 kg	45 mm
09-096D	GeoFlex Exhaust-220 ø102 mm x 15 meters pcs	9,9 kg	45 mm
09-097A	GeoFlex Exhaust-220 ø127 mm x 5 meters pcs	4,5 kg	65 mm
09-097B	GeoFlex Exhaust-220 ø127 mm x 7,5 meters pcs	6,7 kg	65 mm
09-097C	GeoFlex Exhaust-220 ø127 mm x 10 meters pcs	9 kg	65 mm
09-097D	GeoFlex Exhaust-220 ø127 mm x 15 meters pcs	13,5 kg	65 mm
09-098A	GeoFlex Exhaust-220 ø152 mm x 5 meters pcs	5,75 kg	85 mm
09-098B	GeoFlex Exhaust-220 ø152 mm x 7,5 meters pcs	8,6 kg	85 mm
09-098C	GeoFlex Exhaust-220 ø152 mm x 10 meters pcs	11,5 kg	85 mm
09-098D	GeoFlex Exhaust-220 ø152 mm x 15 meters pcs	17,2 kg	85 mm
09-099A	GeoFlex Exhaust-220 ø200 mm x 5 meters pcs	7,6 kg	125 mm
09-099B	GeoFlex Exhaust-220 ø200 mm x 7,5 meters pcs	11,4 kg	125 mm
09-099C	GeoFlex Exhaust-220 ø200 mm x 10 meters pcs	15,2 kg	125 mm
09-099D	GeoFlex Exhaust-220 ø200 mm x 15 meters pcs	22,8 kg	125 mm

As standard it is delivered in black/black, but by request it can be delivered in black/yellow, black/blue, black/green or black/red, minimum buy is 30 meter. Expect a delivery time of 4 weeks.

GeoFlex Kevlar HT (-60°C to +260°C - briefly 300°C)**Kevlar Silicone w/galv. steel coil**

Use:
Extraction of hot vapours,
exhaust or dust

Art. No.	Description	Weight	Bend
09-190	GeoFlex Kevlar ø83, per meter	0,95 kg/m	34 mm
09-191	GeoFlex Kevlar ø102, per meter	0,86 kg/m	40 mm
09-192	GeoFlex Kevlar ø127, per meter	1,07 kg/m	48 mm
09-193	GeoFlex Kevlar ø152, per meter	0,83 kg/m	55 mm
09-194	GeoFlex Kevlar ø160, per meter	0,89 kg/m	58 mm
09-195	GeoFlex Kevlar ø203, per meter	1,1 kg/m	70 mm
09-196	GeoFlex Kevlar ø254, per meter	1,4 kg/m	86 mm
09-197	GeoFlex Kevlar ø305, per meter	1,67 kg/m	102 mm

(Kevlar-reinforced 300° hose - lengths of 1 to 10 m)

GeoFlex Exhaust HT-450 (-60°C to +450°C - briefly 500°C)**Silicone coated fiber glas w/galv. profile**

Use:
Extraction of hot vapours,
exhaust or dust

Art. No.	Description	Weight	Bend
09-130	GeoFlex Exhaust HT-450 ø102, per meter	1,29 kg/m	51 mm
09-131	GeoFlex Exhaust HT-450 ø127, per meter	1,60 kg/m	61 mm
09-132	GeoFlex Exhaust HT-450 ø152, per meter	1,34 kg/m	38 mm
09-133	GeoFlex Exhaust HT-450 ø160, per meter	1,46 kg/m	40 mm
09-134	GeoFlex Exhaust HT-450 ø203, per meter	1,81 kg/m	48 mm

Available in lengths of 1 to 10 m

GeoFlex Exhaust HT-650 (-60°C to +600°C - briefly 700°C)**Special high temp-weave/stainless coil**

Use:
Extraction of hot vapours,
exhaust or dust

Art. No.	Description	Weight	Bend
09-159	GeoFlex Exhaust HT-650 ø102, per meter	2,1 kg/m	53 mm
09-161	GeoFlex Exhaust HT-650 ø127, per meter	2,6 kg/m	63 mm
09-163	GeoFlex Exhaust HT-650 ø152, per meter	2,11 kg/m	73 mm
09-164	GeoFlex Exhaust HT-650 ø160, per meter	2,25 kg/m	77 mm
09-165	GeoFlex Exhaust HT-650 ø203, per meter	2,79 kg/m	93 mm
09-166	GeoFlex Exhaust HT-650 ø250, per meter	3,53 kg/m	115 mm
09-169	GeoFlex Exhaust HT-650 ø315, per meter	4,35 kg/m	139 mm

Available in lengths of 1 to 10 m

GeoFlex Exhaust HT-1100 (-60°C to +900°C - briefly 1100°C)**3 ply special high temp-weave/stainless coil**

Use:
Extraction of for ex. exhaust from
locomotives, tanks and more with
very high temperatures.

Art. No.	Description	Weight	Bend
09-140	GeoFlex Exhaust HT-1100 ø102, per meter	2,8 kg/m	64 mm
09-141	GeoFlex Exhaust HT-1100 ø127, per meter	3,43 kg/m	77 mm
09-142	GeoFlex Exhaust HT-1100 ø152, per meter	3,07 kg/m	89 mm
09-143	GeoFlex Exhaust HT-1100 ø160, per meter	3,27 kg/m	94 mm
09-144	GeoFlex Exhaust HT-1100 ø203, per meter	4,03 kg/m	114 mm

Available in lengths of 1 to 10 m

GeoFlex Standard (-30°C to +140°C)

PVC / ALU



Use:
Extraction of air, welding smoke
and fumes.

Art. No.	Description	Weight	Bend
09-012	GeoFlex Standard ø50, 10 meter pcs	0,14 kg/m	29 mm
09-002	GeoFlex Standard ø82, 10 meter pcs	0,16 kg/m	48 mm
09-003	GeoFlex Standard ø102, 10 meter pcs	0,17 kg/m	59 mm
09-005	GeoFlex Standard ø127, 10 meter pcs	0,21 kg/m	74 mm
09-001	GeoFlex Standard ø152, 10 meter pcs	0,32 kg/m	88 mm
09-004	GeoFlex Standard ø160, 10 meter pcs	0,35 kg/m	93 mm
09-000	GeoFlex Standard ø203, 10 meter pcs	0,46 kg/m	118 mm
09-019	GeoFlex Standard ø254, 10 meter pcs	0,61 kg/m	147 mm

GeoFlex Weld (-10°C to +60°C - briefly 110°C)

PVC / Polyester weave steel coil



Use:
Extraction of wood dust, metal dust,
oil and petrol fumes.
Suitable for wood- food- and
pharmaceutical industry.

Art. No.	Description	Weight	Bend
09-306	GeoFlex Weld ø80	0,19 kg/m	43 mm
09-307	GeoFlex Weld ø102	0,24 kg/m	54 mm
09-310	GeoFlex Weld ø127	0,32 kg/m	67 mm
09-312	GeoFlex Weld ø152	0,37 kg/m	79 mm
09-313	GeoFlex Weld ø165	0,46 kg/m	86 mm
09-314	GeoFlex Weld ø203	0,60 kg/m	105 mm
09-315	GeoFlex Weld ø250	0,77 kg/m	129 mm

Available in lengths of 2, 3, 4, 5 or 10 m. Price per meter.

GeoFlex PUR (-40°C to +90°C - briefly 125°C)

PUR, antistatic



Use: Extraction of wood dust, flour dust
oil and petrol fumes.
Suitable for wood- food- and
pharmaceutical industry.

Art. No.	Description	Weight	Bend
09-403	GeoFlex PUR ø50	0,37 kg/m	33 mm
09-407	GeoFlex PUR ø80	0,57 kg/m	48 mm
09-408	GeoFlex PUR ø100	0,67 kg/m	58 mm
09-410	GeoFlex PUR ø125	0,83 kg/m	71 mm
09-412	GeoFlex PUR ø150	0,99 kg/m	83 mm
09-412A	GeoFlex PUR ø160	1,05 kg/m	88 mm
09-414	GeoFlex PUR ø200	1,33 kg/m	108 mm
09-415	GeoFlex PUR ø250	1,64 kg/m	133 mm

Available in lengths of 5, 10 or 15 m. Price per meter.

GeoFlex High (-40°C to +60°C) Black, antistatic

EVA



Use: Extraction of exhaust, dust, air
and welding fumes.

Art. No.	Description	Weight	Bend
09-007	GeoFlex High ø32 - up to 20m	0,27 kg/m	80 mm
09-008	GeoFlex High ø38 - up to 20m	0,32 kg/m	100 mm
09-009	GeoFlex High ø51 - up to 20m	0,44 kg/m	150 mm
09-082	GeoFlex High ø64 - up to 15m	0,54 kg/m	250 mm

Lengths: Per meter, up to 20 m. Price per meters

GeoFlex High (-40°C to +60°C) Yellow, not antistatic

EVA



Art. No.	Description	Weight	Bend
09-020	GeoFlex High ø45 - up to 20m	0,38 kg/m	125 mm
09-010	GeoFlex High ø76 - up to 10m	0,65 kg/m	300 mm

Lengths: Per meter, up to 20 m. Price per. meters

Connection piece for connecting 2 hoses



Art. No.	Description
57-002	Connecting piece ø80 mm
57-003	Connecting piece ø100 mm
57-001	Connecting piece ø125 mm
57-013	Connecting piece ø150 mm
57-004	Connecting piece ø160 mm
57-005	Connecting piece ø200 mm

Hose clamps



Art. No.	Description
09-033	Hose clamp ø70 – 90 mm
09-034	Hose clamp ø90 – 110 mm
09-035	Hose clamp ø120 – 140 mm
09-036	Hose clamp ø150 – 170 mm
09-037	Hose clamp ø190 – 210 mm

01-499	Rubber band ø125-160 black
01-498	Rubber band ø200 black

Quick coupling for medium pressure



Art. No.	Description
05-005	Quick coupling 80V for wall mounting
05-008	Quick coupling 80L hanging
05-006	Quick coupling 100V for wall mounting
05-009	Quick coupling 100L hanging
05-011	Hose piece for quick coupling 80V/L
05-014	Hose piece for quick coupling 100V/L
05-013	Hose piece 80/100 for quick coupling 80V/L
06-400	Quick coupling 80 VL with end cover
06-401	Quick coupling 100 VL with end cover
06-402	Quick coupling 125 VL with end cover
06-403	Quick coupling 150 VL with end cover
06-404	Quick coupling 160 VL with end cover
06-405	Quick coupling 200 VL with end cover
06-409	Switch for Quick coupling
06-410	Hose piece 80 VL
06-411	Hose piece 100 VL
06-412	Hose piece 125 VL
06-413	Hose piece 150 VL
06-414	Hose piece 160 VL
06-415	Hose piece 200 VL
91-285	Quick coupling ø80 VL
91-286	Quick coupling ø100 VL
91-287	Quick coupling ø125 VL
91-288	Quick coupling ø150 VL
91-289	Quick coupling ø160 VL
91-290	Quick coupling ø200 VL

Hose holder



Art. No.	Description
07-016A	Hose holder ø100/150 mm - wall mounted